

CERTIFICATE OF QUALITY

Page: 1/1
 Date of issue: April 14th, 2010

1.	PRODUCT NAME A M I K O L Mould Resistant Interior Wall Paint
2.	GENERAL DESCRIPTION Interior water – based emulsion paint intended for decorative protection of surfaces , where the development and growth of wall mould is expected due to macro and micro climate conditions.
3.	COMPOSITION Water – based polymers, cellulose ether, titanium dioxide, fillers, special additives.
4.	PHYSICAL AND CHEMICAL PROPERTIES
4.1.	APPEARANCE : viscous liquid
4.2.	COLOUR : white, color shades
4.3.	DENSITY (kg/dm ³ /20°C) : app.1,42
4.4.	pH (20°C) : 9,0 – 10,5
4.5.	FLASH POINT : /
4.6.	SOLIDS CONTENT (%) : 60,0 – 64,0
4.7.	WVTR μ (-) : $\mu < 3000$
4.8.	VALUE Sd (m) , d = 100 μ m : Sd < 0,30 (EN ISO 7783 – 2 , Class 2, medium)
4.9.	WET SCRUB RESISTANCE : resistant, Class 1 (EN 13300)
4.10.	CONTRAST RATIO : Class 1 at a spreading rate 7,0 m ² / l (EN 13300)
4.11.	GLOSS : Semi gloss (EN 13300)
4.12.	VOC : max. 3,0 g/l
5.	HAZARDS IDENTIFICATION This product is classified as NOT HAZARDOUS according to EC – directive EU 1999/45/EC.
6.	TEST REPORTS FPL- Stuttgart, Germany, Report AT 073d/04, 22. 12. 2004
7.	The document was issued with the intention to prove the quality of the product according to specific requirements.

R&D Coordination Manager
 Damjan Saksida, B. Sc. Chem. Techn.

Saksida



10